



Specifications:
 Glycol Feed Package designed to pump glycol upon system pressure drop with low level cut off.
 Comes complete with steel tank, pump, stand (frame), control panel, low level, flooded suction, strainer, check valve, pressure switch, pressure indicator, pressure relief and isolation valve.

Standard Settings:
 Pump Output: 1.3 **GPM**
 Pressure Cut-In: 20 **PSI**
 Pressure Cut-Out: 40 **PSI**
 Pressure Relief: 50 **PSI**

Materials of Construction:
 Epoxy, Brass, Carbon Steel, Polyethylene, PVC and Polypropylene

Voltage:	115 VAC	1 PHS	60 PHS
Max. Temp.:	180	°F	
Max. Press:	150	PSI	
Weight:	234	LBS	

12	X	X
11	X	X
10	X	X
9	X	X
8	X	X
7	X	X
6	X	X
5	X	X
4	X	X
3	X	X
2	X	X
1	X	X

#	Part	Description
---	------	-------------



Phone: 714-257-9165
 Fax: 714-257-9215
www.gtpcompany.com

Drwn By: JC	Related Items: X
Date: 12/1/10	
Scale: NTS	
Rev: A	

D	X	X
C	X	X
B	X	X
Rev.	Description	Date

Notes:
 1)

Notice
 This drawing and its content are for the specific use of GTP customers only. It is not to be duplicated or copied without expressed written content of General Treatment Products, Inc. We Reserve the right to modify this drawing with out notice.

Description:
 30GL High Temp Glycol Feed Package
Model:
 GP30-H4-1