

GTP "P" and "CP" Series

Polyethylene Industrial Tanks

Specification 01600040 Rev. A

Written: April 2006

Page 1 of 1



✧ 1.0 DESCRIPTION

1.1 POLYETHYLENE TANK: Shall be supplied by General Treatment Products, or approved equal and be constructed of high density, low linear polyethylene and have easy to read, sprayed on gallon markers. When supplied, cover shall be show box style of ample size for removal to fill or view contents.

✧ 2.0 MATERIALS

2.1 TANK: Shall be constructed of high density, low linear polyethylene as manufactured by Exxon Mobil 8460 LLDPE or approved equal. Tank to be designed and supplied as:

- Cylindrical open top with flat bottom
- Cylindrical open top with conical bottom

2.2 GALLON MARKERS: Shall be spray on type with paint designed for plastic surfaces. Increments shall be acceptable for size or volume of tank.

2.3 COVER: Shall be shoe box style of ample size and supplied as

- Flat shoe box style
- Flat shoe box style with 1/3 Aluminum hinge
- Sealed with threaded entry

2.4 FITTINGS: Factory supplied fittings shall be either spun-welded to polyethylene tank or be gasketed PVC and EPDM bulkhead style that is replaceable in field. All tanks ordered with fittings installed will require customer approved drawing.

✧ 3.0 WARRANTY: General Treatment Products Industrial Polyethylene Tanks are guaranteed for two years from date of shipment against manufacturing defects in material and workmanship which develop in the service for which they are designed. We will repair or replace a defective part of this system when returned to our factory with freight prepaid; providing that the part is found to be defective upon inspection. We assume no liability for labor and/or other expenses in making repairs or adjustments.